

Total No. of Questions : 10]

SEAT No. :

**P3984**

**[4959]-1038**

[Total No. of Pages : 3

**B.E. (Mechanical)**

**GAS TURBINE & PROPULSION (Elective - II)**  
**(2012 Course) (Semester - I) (402045A) (End Sem.)**

*Time : 2½ Hours]*

*[Max. Marks : 70*

*Instructions to candidates:*

- 1) *Answer Q1 or Q2, Q3 or Q4, Q5 or Q6, Q7 or Q8, Q9 or Q10.*
- 2) *Neat diagrams must be drawn wherever necessary.*
- 3) *Figures to the right indicate full marks.*
- 4) *Assume suitable data if necessary.*

**Q1) a)** Write assumptions made in analysis of compressible fluid flow under steady state conditions and derive continuity equation. **[6]**

b) An aeroplane is flying at a speed of 800 kmph at a high altitude where the atmospheric air temperature is  $-73^{\circ}\text{C}$ . Calculate the sonic velocity and its Mach number. Assume  $R = 287 \text{ Nm/kg.K}$ . **[4]**

OR

**Q2) a)** In an oil gas turbine plant, air is compressed from a pressure of 1 bar and temperature of 300K upto a pressure of 5 bar. The oil used has calorific value of 42500 kJ/kg and the combustor efficiency is 95%. Hot gases leaves the combustion chamber at 1000 K. The isentropic efficiency of the turbine & compressor are 90% and 85% respectively. Assuming the mass flow rate of air at 1kg/s, find power output of the plant. **[6]**

b) With the help of neat diagrams, explain the effect of reheat gas turbine cycle on specific work output and thermal efficiency. **[4]**

**Q3) a)** Compare the steam & gas turbine power plants. **[6]**

b) Mention the various advantages & disadvantages of the pulse jet engines. **[4]**

OR

**P.T.O.**

**Q4) a)** In a gas turbine cycle, air at  $27^{\circ}\text{C}$  and 0.98 bar is compressed to 6 bar. The temperature of air is increased to  $750^{\circ}\text{C}$  as it passes through the combustion chamber. The isentropic efficiencies of compressor & turbine are 0.8 and 0.85 respectively. Determine the efficiency of the plant. [6]

b) Define:-

i) Propulsive power,

ii) Propulsive efficiency [4]

**Q5) a)** A single stage impulse turbine has the blade velocity of 300 m/s. The gas velocity at entry to stage is at 800 m/s having the nozzle angle of  $16^{\circ}$ . The rotor blades are symmetrical. Assuming a friction factor of 0.9, find:

i) Work output

ii) Utilisation factor for the stage,

iii) Stagnation temperature drop in turbine,

iv) Stagnation pressure ratio if inlet temperature is 1000 K and the total head isentropic efficiency is equal to utilisation factor. [10]

b) Discuss the effect of nozzle angle on work output in case of impulse turbine. [6]

OR

**Q6) a)** Derive the equation of the condition of maximum utilisation factor for a velocity compounded impulse turbine. State clearly the assumptions made. [10]

b) Discuss the performance curves of gas turbines. [6]

**Q7) a)** An axial flow compressor having 8 stages and 50% reaction design compresses air in the pressure ratio of 4:1. The air enters the compressor at 20°C and flows through it with a constant speed of 90 m/s. The rotating blades of the compressor rotates with a mean speed of 180 m/s. Take isentropic efficiency of the compressor as 82%. Calculate:

- i) Work done by the machine
- ii) Blade angles

Take,  $\gamma = 1.4$  &  $C_p = 1.005$  kJ/kg K. **[12]**

b) Differentiate between turbine blading & axial flow compressor blading. **[6]**

OR

**Q8) a)** Explain the following:

- i) flow coefficient,
- ii) rotor pressure flow coefficient,
- iii) rotor enthalpy drop coefficient,
- iv) diffuser enthalpy drop coefficient **[12]**

b) Explain the design and off - design characteristics of an axial flow compressor. **[6]**

**Q9) a)** Discuss how a reactive mixture is formed in a combustion chamber of a gas turbine with all steps involved. **[8]**

b) What are the factors involved in combustion of liquid fuel in the combustor? What are the aspects considered in design of a combustor? **[8]**

OR

**Q10) a)** Explain the annular combustion chamber with a neat sketch and also explain which type of method is used in it for flame stabilisation. **[8]**

b) Why cooling of flame tubes is necessary and what are the methods employed? Discuss various methods with the help of neat sketches. **[8]**

**x x x**